PLASTER REPAIR KIT

This method statement contains the details about the usage and application of the Repair kit for the bloomstone series. We will be covering the rectification of cracks, bumps, paint peels, dents, and scratches.

1- The repair kit comes with 8 items

A) Repair medium
B) Touch-up paint
C) Topcoat
D) Paintbrush
E) Sanding paper 1000 grit &2000 grit
F) De-greaser/ cleaning spray
G) Cleaning Cloth
H) Additional Hardware

2- Items A to G will be used for the damages stated in the scope of this method statement.

See the instruction video

Steps

1) Check the surface for any damages and make sure to use the right material with the correct combination.
2) Use cleaning spray from the kit to remove any grease from the surface, once dry, start sanding with 1000 grit sandpaper and wipe off the residue.
3) Now apply the repair medium directly over the crack or dent in small portions as too much application may lead to bumps that will be visible after the top Coat. You can apply the second coat of repair medium after sanding the first layer after drying. Once dry and all cracks and dents filled, sand the repair medium to match the levels of the substrate.
4) After step 3 make sure there are no Bumps and cracks/ pinholes left, if none, we can start with the application of touch-up paint with the use of a brush. Let the first coat dry and sand it off gently to remove brush strokes and reapply a coat of touch-up paint. Once dry, sand it again gently to remove brush strokes.
5) Now using the paintbrush you can proceed with applying the top Coat (clear coat). Follow the steps same as we did for touch-up paint. 2 coats of top Coat will be good.
6) After the top Coat dries, please use 2000 grit sandpaper very gently to remove any dust and merge the newly painted surface to match with old finish.
7) Leave the repaired products to cure for a minimum of 72 hours.
8) If there are any doubts regarding the method statement, please refer to the video for your reference.

Safety

1) Wear latex gloves, all materials in this repair kit are safe as the finishes are REACH & GREENGUARD compliant.
2) Use eyeglasses.
3) In case of accidental intake of any of the materials of the repair kit, kindly contact the medical Centre ASAP.
4) In case of direct contact with eyes, rinse thoroughly with clean water and reach the nearest medical center at the earliest.
5) Some people might be allergic to a few substances in the paint, wearing a mask will help avoid any allergies.